

This MSDS is prepared according to EU 453/2010 regulations.

Product Name: FP 1600 FLO YELLOW

1. PRODUCT NAME AND COMPANY INFORMATION

Chemical Characteristic	PVC containing paste
•	Printing paste for the textile screen printing industry
	ÖZANADOLU KİMYA SAN. Ve TİC. A.Ş. Mahmutbey Merkez Mah. Karaoğlanoğlu Cd.Servet Sk.No:8 Bağcılar/İstanbul Tel:0 212 446 92 92 Fax:0 212 446 00 99 Mail: <u>istanbul@inkuin.com</u>
Emergency Information	0 212 446 92 92

2. HAZARDS IDENTIFICATION

This product, is not dependent on classifications in terms of physicochemical, toxicological and ecotoxicologically. Given components at composition section are only informational purposes only.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Compound Name	Weight %	Cas No	Hazard Class	H Phrases	Limit for Classification
Dioctyl terephthalate	45-50	6422-86-2	-	-	-
PVC	45-50	9002-86-2	-	-	-
Flo Yellow Pigment	5-10	-	-	-	-

For H Phrases text look at section 15.

4. FIRST-AID MEASURES

On eye contact	Rinse thoroughly for 15 Minutes and consult a doctor immediately.
On skin contact	Have not important effects .Wash throughly with water. If possible use working gloves.
On Inhalation	Have not important effects. After much inhalation go fresh air.
On Swallowing	After swallowing seek medical advice. Show the label and package to doctor.

Page 1/5



 Form No
 :60

 Date
 14/10/2009

 Revision
 02

 Revision date
 :10/02/2016

This MSDS is prepared according to EU 453/2010 regulations.

Product Name: FP 1600 FLO YELLOW

5. FIRE – FIGHTING MEASURES

Suitable Extinguishing Media	Water mist, foam dry powder, CO2. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable Extinguishing Media	There is no particular unsuitable media. Do not use only water directly
Specific Hazards as a result of fire.	Burning products in case of fire (Carbon dioxide, toxic pyrolysis residues, etc.) Do not inhale.
Precuations against case of fire.	Helmet, Fire-resistant clothing (Arm, leg and waist raound banded, fire- resistant jacket and throusers), gloves (fire protecting, cutting preventive and dielectric), Face protective and Positive pressure Mask covering operator's face totally or in case of being big amount of smoke, clean air inhalator (tube and masked).

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Please look at item 8. If material is spilled the ground may be slippery.
Environmental Precautions	Do not discharge to the sewage, surface water and soil.
Methods of Cleaning	Close the drains (clogging risk). Use absorbent materials for cleaning up. Sweep up the stained places and dispose according to legal regulations.

7. HANDLING AND STORAGE

Handling	Precautions for safe handling: Assure the working place a well ventilated place. Keep closed the cover of goods well. Precautions for Fire and explosition danger: There is no special
Storage	Conditions for safe storage: Keep container tightly closed and dry; store in a cool place at 5°C- 25°C. Suitable Packaging: Polyethylene Common storage warnings: Not required.

Page 2/5



This MSDS is prepared according to EU 453/2010 regulations.

Product Name: FP 1600 FLO YELLOW

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

	In unwell ventilated place Respiratory protection in needed in case
	there is a spray processing application.
Hand protection	Suitable protection gloves
Eye protection	Protection googles
Skin protection	Working Clothes are suggested.
	Please follow general condition of chemical applications

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical Form	Paste	
Colour	Flo yellow	
Odour	Weak Odour	
Melting Point	Not Applied	
Boiling Point	Not Applied	
Flashing Point	Not Applied	
Explotion Danger	Not Explosive	
Steam pressure	Not Applied	
Self Flammability	Product is not Self-Flammable	
Solubility with Water	Insoluable with Water	
Ph	Not applied	
Viscosity	Sp:7 rpm: 1 cp: 500,000 – 2,000,000 mPas (Brookfield DV II +)	
Difference factor	Not Applied	

10. STABILITY AND REACTIVITY

The product is stable and no hazardous reaction will occur in normal condition. In decomposition and fire hazardous vapour may occur.



 Form No
 :60

 Date
 14/10/2009

 Revision
 02

 Revision date :10/02/2016

This MSDS is prepared according to EU 453/2010 regulations.

Product Name: FP 1600 FLO YELLOW

11. TOXICOLOGICAL INFORMATION

It is not seen any bad effects to human health after exposure. We suggest working in suitable and well ventilated working places. Preparat, especially for sensitive individuals, by inhalation / or introsusception by skin /or eye contact and /or by swallowing it could cause some mild effects on health.

Acute Data : Analojic data, briefly; LD50>2000 mg/kg rat.

Toxicologic extra information:

General European Community Regulation on Classification for product preparation is not subject to classification according to the latest version of the calculation method, based on the experience we gained and the data received from our suppliers; If used according to the specifications and disposal of this product is not harmful.

12. ECOLOGICAL INFORMATION

Biodegradable: Product according to OECD criterias, because of its nature is Biodegradable. In biological treatment plant elemination can be done with foliculation, defecation and activated clay adsorbtion. Ecotoxicity Effects: Water Toxicity:(OECD 202,section1,DIN38412,section11,DEV L11) Dafnia Toxicity Ec50>1000 mg/l (Dapnia manga,48 hours)

13. DISPOSAL CONSIDERATIONS

Disposal, in accordance with national and local regulations should be done or delivered to a company with authorized waste management.

Contaminated Packaging

Contaminated packaging, recycling in accordance with national laws relating to waste management and should be sent or to be destroyed..

Page 4/5



 Form No
 :60

 Date
 14/10/2009

 Revision
 02

 Revision date :10/02/2016

This MSDS is prepared according to EU 453/2010 regulations.

Product Name: FP 1600 FLO YELLOW

14. TRANSPORT INFORMATION

Not classified as hazardous under transport regulations (ADR, RID, IMDG ,ICAO/IATA)

15. REGULATORY INFORMATION

Hazard Statements;	H302: Harmful if swallowed
Precuation Suggestions;	H304: May be fatal if swallowed and enters airways. P264: Wash thoroughly after handling P270: Do not eat, drink or smoke when using this product.

16. OTHER INFORMATION

GENERAL RESOURCES

- 1- 1999/45/AT
- 2- 67/548/AET
- 3- Regulation (EC) 1907/2006 (REACH)
- 4- The Merck Index.Ed.10
- 5- Handling Chemical Safety
- 6- Raw material's MSDS

PS: This MSDS has been prepared in the light of the data which we get from our current updated information and our suppliers. The purpose of this Safety Data Sheet is to describe the products in terms of safe handling, use, processing, storage, transportation, disposal and release. This MSDS does not imply a warranty concerning composition, properties or performance. Also it does not replace the legal validity of a contract.

Page 5/5