

DE 2305 CMYK PASTE PHOTOGRAPHIC PASTES

- PRODUCTS** : DE 2305 CMYK PASTE–Photographic Paste - Over Discharge
- FEATURES** : Applied over grounds printed with ecologic discharge,
Easily used in high tram meshes,no blockage in template,
High washing fastness,
Complies with ecologic standards.
- APPLICATION** : Coloured DE2305 CMYKPASTE is applied to dark coloured fabrics printed with DE Ecologic Discharge. Paying attention to fixing conditions is essential for better results.

Sample Formulation:

GROUND PRINT

- DE2100ECOCLEAR :80gr
DE2105ECOWHITE: 20gr
DE2110ECOACTIVATOR : 7gr
RB2602CURAFast :2-3gr (Fastness Increaser)

UPPER LAYER PRINT

- DE2305CMYKPASTE: 100gr
PG2816 RED : 4gr
RB2602 CUREFAST : 2-3gr(Fastness Increaser)

- COLOUR** : Clear
- PH** : 8,0± 0,5
- VISCOSITY** : Clear:(Brookfield25°CSp:6,Rpm:10)35.000-80.000cp
- SCREEN** : 62/T-77/T-120/T Treads/cm is recommended.
- FIXING** : Fixing temperature and timw;160°C-170°C 1,5-2 minutes.
- CLEANING** : Screens and other equipments may be easily washed by pressure water.
- PACKING** : Blue 30kg packing.

Note : Above mentioned qualified data is obtained from our R&D tests done in our own R&D labs. Supplied as General Knowledge and Information only and should not be considered as a Warranty Information.Printing Quality may change for different company conditions. Please start your production process after completing your own trial tests. Please stir before using the product and keep the product in room temperature.