

PG GROUP PIGMENTS

- PRODUCTS** : **PG GROUP PIGMENTS**
- FEATURES** : Used for colouring of water based pastes,
High colour productivity,
High light fastness,
Totally 22 colour range,
All pigments are complying with ecologic standards excluding the
fluorescent colours.
Fluorescent colours include Formaldehyde.
- APPLICATION** : Applied with carrier paste or elastic equipments. They are not applied alone.
- COLOUR** :
- PG 2800 YELLOW–Yellow
 - PG 2805 GOLD–GoldYellow
 - PG 2810 ORANGE–Orange
 - PG 2816 DARKRED–Dark Red
 - PG 2817 SCARLET–Scarlet
 - PG 2818 SUPERRED–Red
 - PG 2820 CARMINERED–Carmine Red
 - PG 2825 MAGENTA–Magenta
 - PG 2830 RUBINE–Claret Red
 - PG 2835 VIOLET–Violet
 - PG 2840 BLUE– Blue
 - PG 2845 NAVYBLUE–Navy Blue
 - PG 2850 TUQUOISE–Turquoise
 - PG 2855 GREEN–Green
 - PG 2860 BROWN–Brown
 - PG 2865 BLACK–Black
-
- PG 2900 FLOYELLOW–Fluorescent Yellow
 - PG 2905 FLOORANGE–Fluorescent Orange
 - PG 2910 FLORED–Fluorescent Red
 - PG 2915 FLOPINK–Fluorescent Pink
 - PG 2920 FLOMAGENTA–Fluorescent Magenta
 - PG 2925 FLOGREEN–Fluorescent Green
- VISCOSITY** : (Brookfield25°CSp:5,Rpm50)500–2000Cp
- SCREEN** : 34/T–43/T Thread/cm is advised.
- CLEANING** : Screens and other equipments may be cleaned easily by pressure water.
- WASHING** : High washing fastness
- PACKING** : Plastic Packing of 1-5ve30kg.

STORAGE : Product should be stored at well ventilated room with between +10°C and +25°C temperature. It should be away from direct sunlight, excess heat and cold. Products should be stored with their sealed container. Expiry date is 12 months from the production date.

IMPORTANT NOTE :

Be carefull about mixing the colours, especially orange(Orange34) and black (Black 7) colour. Because when these two colours are mixed, undesired carcinogenic aromatic amines 3,3-dichlorobenzidine can be detected. This way should not be used. Different colour combinations should be used.

Note : Above mentioned qualified data is obtained from our R&D tests done in our own R&D labs. Supplied as General Knowledge and Information only and should not be considered as a Warranty Information. Printing Quality may change for different company conditions. Please start your production process after completing your own trial tests. Please stir before using the product and keep the product in room temperature.