

## **PA 1443 BONDOFOIL PLASTISOL FOIL ADHESIVE**

- PRODUCTS** : **PA 1443 BONDOFOIL**– Plastisol foil adhesive
- FEATURES** : Phtha-Free oil based pastes,  
Comfortable and long term working condition in the screen,  
Special formulation for good washing fastness for foil printing
- APPLICATION** : PA 1443 BONDOFOIL is a special ink which has got special formulation for foil printing. This ink is printed on the fabric as a foil adhesive. It can be printed with standart flat screens and also it can be printed with thick screens to obtain high density foil effects. After printing, fabric should be cured. Then foil is applied on the adhesive surface by heating press. Pressing temperature, time and bar; 160°C-170°C, 5-20 seconds, 5-6 bars. (Type and features of foil should be taken into consideration)
- COLOUR** : Ecu
- VISCOSITY** : (Brookfield25°CSp:7,Rpm:1)>1.000.000Cp
- SCREEN** : 32/T-55/T Threads/cm is recommended.
- FIXING** : Fixing temperature and time;160°C-170°C,1,5-3minutes.
- CLEANING** : Screens and other equipments may be easily washed with synthetic thinner.
- WASHING** : High washing and rubbing fastness.
- PACKING** : Plastic Packing of 6 kg.

Note : Above mentioned qualified data is obtained from our R&D tests done in our own R&D labs. Supplied as General Knowledge and Information only and should not be considered as a Warranty Information. Printing Quality may change for different company conditions. Please start your production process after completing your own trial tests. Please stir before using the product and keep the product in room temperature.