

EP 1924

PVC& PHTHALATE-FREE BONDOFOIL

- PRODUCTS** : **EP 1924 BONDOFOIL**
- FEATURES** :
- PVC&Phtha-Free oil based pastes,
 - Comfortable and longterm working condition in the screen,
 - Compliance with ecological standarts
 - Special formulation for good washing fastness for foil printing
- APPLICATION** : EP 1924 BONDOFOIL is a special ink which has got special formulation for foil printing. This ink is printed on the fabric as a foil adhesive. It can be printed with standart screens and also it can be printed with thick screens to obtain high density foil effects. After printing, fabric should be cured. Then foil is applied on the adhesive surface by heating press. Pressing temperature, time and bar; 160°C-170°C, 5-20 seconds, 5-6 bars. (Type and features of foil should be taken into consideration)
- COLOUR** : Ecu
- VISCOSITY** : (Brookfield25°CSp:7,Rpm:1)500,000–2,000,000mPas
- SCREEN** : 32/T-55/T Treads/cm is advised.
- FIXING** : Fixing temperature and time;165°C-175°C'de,1,5-2minutes.
- CLEANING** : Screen and all other equipments may be cleaned by synthetic thinners.
- WASHING** : Should be reverse washed under 40C with sensitive program.
- PACKING** : Plastic Packages of 5 Kg.

Note :Above mentioned qualified data is obtained from our R&D tests done in our own R&D labs. Supplied as General Knowledge and Information only and should not be considered as a Warranty Information. Printing Quality may change for different company conditions. Please start your production process after completing your own trial tests. Please stir before using the product and keep the product in room temperature.