

## FP PHTHANON SERIES PHTHALATE FREE PLASTISOL

- PRODUCT** : **FA 1895 STRECH BASE**
- FEATURES** : Phthalate Free,  
Short flash cure time, Appropriate for prints over 100% Cotton,Cotton/Polyester,
- APPLICATION** : FA 1895 STRECH BASE is ready to use transparent ink. It can be used alone or mixed with Phtanon series other plastisol. It is used for increasing the flexibility of plastisol ink on the highly elastic fabrics. Also it gives lower temperature curing possibility like 140°C.
- VISCOSITY** : (Brookfield 25°C Sp:7,Rpm:0,5) 200.000Cp and over.
- SCREEN** : 43/T-101/TThreads/cm.
- FIXING** : Fixing degree and time;140°C-170°C,1.5-2 minutes.
- CLEANING** : Templates and other equipments may be easily cleaned by synthethic thinner.
- WASHING** : If there are Polimerization conditions, washing fastness is 60°C. But if there are minimumpolymerization conditions washing fastness is 40°C. Not appopriate for dry cleaning and ironing.
- PACKING** : Plastic Packing of 5kg.
- STORAGE** : Should be kept away from sunlight, extreme heat and cold. It should be storage unifrom environment with 5oC - 25oC. Please be sure that, containers are always tightly closed. The expiration date is 3 months from date of manufacture.

Note : Above mentioned qualified data is obtained from our R&D tests done in our own R&D labs. Supplied as General Knowledge and Information only and should not be considered as a Warranty Information.Printing Quality may change for different company conditions. Please start your production process after completing your own trial tests. Please stir before using the product and keep the product in room temperature.