



DP2300 CMYK PASTE PHOTOGRAPHIC PRINT PASTE

- PRODUCTS** : **DP 2300 CMYK PASTE**– Photographic Print Paste
- FEATURES** : Gives an opportunity to work in high tram photographic designs & high mesh numbers, no choking in the screen, water based product. Complies with ecologic standards, Ekoteks 100 Class I.
- APPLICATION** : May be used in light coloured fabrics. For dark fabrics, DP series white pastas must be printed firstly as a undercoat. Colouring may be done by PG Group Pigments in max. %3 percentage. Easy and comfortable printing in high mesh numbers and high tram photographic designs. Printed fabric is recommended to be fixed in 165°C and in 1,5-2minutes.
- COLOUR** : Clear
- PH** : 8,0± 0,5
- VISCOSITY** : Clear:(Brookfield25°CSp:6,Rpm:10)20.000-50.000cp
- SCREEN** : 62/T-77/T-120/TTreads/cm is recommended.
- FIXING** : Fixing temperature and time;160°C-170°C 1,5-2minutes.
- CLEANING** : Screens and other equipments may be easily washed by pressure water.
- PACKING** : 30kg packing.

Note : Above mentioned qualified data is obtained from our R&D tests done in our own R&D labs. Supplied as General Knowledge and Information only and should not be considered as a Warranty Information. Printing Quality may change for different company conditions. Please start your production process after completing your own trial tests. Please stir before using the product and keep the product in room temperature.