

RB 2510PEARLPASTE

- FEATURED** : High Coverage.
Very soft handling and bright. Very easily and comfortably used in Filmdruck and Rotation Print.
This water based print paste gives the desired pearl view to be used in textile printing.
- APPLICATION** : Fully prepared and ready to use paste. 5–10gr/kg PG Group pigments may be used for colouring. To increase and strengthen rubbing, washing fastness and the print durability, %1-3 percentage RB 2600 Oxal or %0,5–1 percentage RB2601 Superfix catalyst may be added.
- COLOUR** : Ecrü Paste in pearl brightness.
- PH** : 8.5± 0,5
- VISCOSITY** : (Brookfield25°CSp:6,Rpm:10)20.000 –25.000Cp
- DENSITY** : 1,06gr/ml
- SCREEN** : 34/T-43/TThreads/cm is recommended.
- FIXING** : Fixing temperature and time;160°C-170°C,2–3minutes
- CLEANING** : Screens and other equipments may be easily washed by pressure water.
- WASHING** : Reverse washing in 40C or below, Sensitive Programs.
- PACKING** : Plastic Packing of 30-60kg

Note : Above mentioned qualified data is obtained from our R&D tests done in our own R&D labs. Supplied as General Knowledge and Information only and should not be considered as a Warranty Information. Printing Quality may change for different company conditions. Please start your production process after completing your own trial tests. Please stir before using the product and keep the product in room temperature.