

## RB 2515 BLACK PUFF

|                    |   |
|--------------------|---|
| <b>FEATURES</b>    | : Deep black puff effect<br>Ready to use paste<br>May be mixed and combined with other RB series acrylic water based pastes.  |
| <b>APPLICATION</b> | : Because of it is fully prepared and ready to use paste, no need to make preparation process. It is used for getting deep black puff effect. For thickening, viscosity may be increased with RB2620 Thickener and a high rotation mixer. To increase and strengthen washing fastness %2-4 percentages RB 2600 OXAL or %0,5-1 percentage RB 2601 SUPERFIX may be added. |
| <b>COLOUR</b>      | : Black   |
| <b>PH</b>          | : 7.5± 0,5  |
| <b>VISCOSITY</b>   | : (Brookfield25°CSp:6,Rpm:10)5000–30.000Cp  |
| <b>SCREEN</b>      | : 43/TThreads/cm is recommended.  |
| <b>FIXING</b>      | : Fixing temperature and time;160°C-170°C, 2minutes.  |
| <b>CLEANING</b>    | : Screens and other equipments may be easily washed by pressure water.  |
| <b>WASHING</b>     | : Reverse washing in 40C or below, Sensitive Programs.  |
| <b>PACKING</b>     | : Plastic Packing of 5 kg   |

Note : Above mentioned qualified data is obtained from our R&D tests done in our own R&D labs. Supplied as General Knowledge and Information only and should not be considered as a Warranty Information. Printing Quality may change for different company conditions. Please start your production process after completing your own trial tests. Please stir before using the product and keep the product in room temperature.