

## **RB 2606 RETARDER RETARDER**

<b>PRODUCTS</b>	: <b>RB 2606 RETARDER</b> –Retardant for water based pastes
<b>FEATURES</b>	: Multiple using features. Used to prevent choking at the screen and brings a easy and comfortable working for the application of water based pastes and inks and especially for the discharge prints. Increases print performance.
<b>APPLICATION</b>	: Can not be used alone. Used by adding %3-5percentage to the water based pastes. Retardant added products should be very well fixed. It is recommended a fixing operation at160°C-170°C, 2-3 minutes for better results.
<b>COLOUR</b>	: Clear
<b>PH</b>	: 11±0.5
<b>VISCOSITY</b>	: (Brookfield25°CSp:2,Rpm:100)50 –300Cp
<b>DENSITY</b>	: 1.03-1.12gr/ml
<b>PACKING</b>	: Plastic Packing of 5-10kg
<b>STORAGE</b>	: Product should be stored at well vantilated room with between +10°C and +25°C temperature. It should be away from direct sunlight, excess heat and cold. Products should be stored with their sealed container. Expiry date is 12 months from the production date.

Note : Above mentioned qualified data is obtained from our R&D tests done in our own R&D labs. Supplied as General Knowledge and Information only and should not be considered as a Warranty Information. Printing Quality may change for different company conditions. Please start your production process after completing your own trial tests. Please stir before using the product and keep the product in room temperature.