

DE 2607 VISCOLOWER VISCOSITY REDUCER

- PRODUCTS** : **DE 2607 VISCOLOWER**– Ecologic Discharge Viscosity Reducer
- FEATURES** : An auxiliary for Ecologic discharge paste for reducing viscosity. No negative effect on washing and colour fastness of product.
- APPLICATION** : Can not be used alone. Must be used together with DE Series Ecologic Discharge paste in %1-3 percentage. This solution is a viscosity reducer and do not affect normal fixing conditions. Suggested fixing conditions can be applied. Must be shaken well before every application.
- COLOUR** : Ecu
- PH** : 8,5±0.5
- VISCOSITY** : (Brookfield25°CSp:2,Rpm:100)30 –100Cp
- DENSITY** : 1-1,5gr/mlgr/ml
- TEMPLATE** : 55T Threads/cm numbered mesh is recommended.(for the prepared discharge paste)
- FIXING** : 160°C-170°C'de,2-3dakikadır.
- PAKETLEME** : Plastic Packing of 5kg.
- STORING** : Keep away from direct sunlight, extreme cold and hot temperature.

Note : Above mentioned qualified data is obtained from our R&D tests done in our own R&D labs. Supplied as General Knowledge and Information only and should not be considered as a Warranty Information. Printing Quality may change for different company conditions. Please start your production process after completing your own trial tests. Please stir before using the product and keep the product in room temperature.