

## **DP 2511 PEARLPASTE SPECIAL PEARL PASTE**

<b>PRODUCTS</b>	: <b>DP2511 PEARLPASTE</b> – Special Pearl Paste
<b>FEATURES</b>	: Fully prepared and ready to use paste for getting Pearl Effect, Soft and slippery touching, Bright and high covering feature, High Elasticity, High Washing Fastness, Complies with ecologic standards.
<b>APPLICATION</b>	: Fully prepared and ready to use paste. For colouring 5–10gr/kg PG Group pigments may be used. % 0,5-1 percentage of RB 2601 SUPERFIX catalyst may be added to increase and strengthen rubbing and washing fastnesses.
<b>COLOUR</b>	: Ecru past in pearl brightness
<b>PH</b>	: 7.5± 0,5
<b>VISCOSITY</b>	: (Brookfield25°CSp:6,Rpm:10)28.000–60.000Cp
<b>DENSITY</b>	: 1,1gr /ml
<b>SCREEN</b>	: 34/T-43/T Threads/cm is recommended.
<b>FIXING</b>	: Fixing temperature and time;160°C-170°C,2–3 minutes.
<b>CLEANING</b>	: Screens and other equipments may be cleaned easily by pressure water.
<b>WASHING</b>	: It is recommended to wash reverse with sensitive programs 40°C or below.
<b>PACKING</b>	: Plastic Packing of 30-60kg.

Note : Above mentioned qualified data is obtained from our R&D tests done in our own R&D labs. Supplied as General Knowledge and Information only and should not be considered as a Warranty Information. Printing Quality may change for different company conditions. Please start your production process after completing your own trial tests. Please stir before using the product and keep the product in room temperature.