

TDS TECHNICAL DATA SHEETS DIAMOND POLYURETHANE WATER BASED

DP 2590 BRILLGEL GLASSY EFFECT BRILLANT GEL

- : DP2590 BRILLGEL- Brillant Gel- Glassy Effect PRODUCTS FREATURES : This paste is used to get brightness effect in water based prints. Complies with ecologic standards. **APPLICATION** : DP 2590 BRILLGEL is used to get more bright and glassy effect after the print. Applied over coloured ground directly before colored. Brings soft touch feature to the applied ground. As a ground, RS Group or DP Group may be used. Best brightness result is when applied over RS Group. When applied over RB Group, %0,5 RB2601 SUPERFIX must be added to both ground RB inks and DP 2590 gel. Prints with Brillant Gel needs well fixing operation. COLOUR : Clear PH : 7±0,5 VISCOSITY : (Brookfield 25°C Sp:6,Rpm:10)40.000–90.000Cp DENSITY : 1,05gr/ml SCREEN : 43/T-62/T Threads/cm and over mesh numbers are recommended.
- **FIXING** : Fixing temperature and time;160°C-170°C,1,5-2 minutes.
- **CLEANING** : Screens and other equipments may be cleaned easily by pressure water.
- **WASHING** : It is recommended to wash with sensitive programs, 40°C or below
- **PACKING** : Plastic Packing of 18-60kg.

Note : Above mentioned qualified data is obtained from our R&D tests done in our own R&D labs. Supplied as General Knowledge and Information only and should not be considered as a Warranty Information.Printing Quality may change for different company conditions. Please start your production process after completing your own trial tests. Please stir before using the product and keep the product in room temperature