

## **DP 2715 BONDOFLOCK SPECIAL FLOCKING BINDER**

- PRODUCTS** : **DP2715 BONDOFLOCK** - Special Water Based Flocking Binder
- FEAUTURES** : Soft and elastic handling feature,  
Excellent binding features,  
Excellent washing fastness,  
No chocking in the screen,  
Complies with Ecologic Standards, Ekoteks100 Class II
- APPLICATION** : DP2715 BondoFlock is used by mixing in % 2.5-3 percentage RB2601 SUPERFIX Catalyst. Should be printed plenty of amounts over fabrics. When printed in plenty of amounts, flocking binder is well binding the flocks thrown by the machine. It is essential to start flocking without any delay after the flocking binder is printed. Fabric that flocking binder is applied should be placed over a metal plate, and the flocking operation should be done by well ground system flocking machine. Needs well fixing.
- COLOUR** : Ecrú
- PH** :  $8,5 \pm 0,5$
- VISCOSITY** : (Brookfield25°CSp:7,Rpm:20)100.000–150.000Cp
- DENSITY** : 1,07gr/ml
- SCREEN** : 27/T-34/T Threads/cm is recommended.
- FIXING** : Fixing temperature and time;170°C-180°C, 2-3minutes.
- CLEANING** : Screens and other equipments may be cleaned easily by pressure water.
- WASHING** : Should be reverse washed in 40°C and below with sensitive program.
- PACKING** : Plastic Packing of 30–60kg.

Note : Above mentioned qualified data is obtained from our R&D tests done in our own R&D labs. Supplied as General Knowledge and Information only and should not be considered as a Warranty Information. Printing Quality may change for different company conditions. Please start your production process after completing your own trial tests. Please stir before using the product and keep the product in room temperature.