

TDS TECHNICAL DATA SHEETS DIAMOND POLYURETHANE WATER BASED

DP 4040 REFLECTGREY

PRODUCTS	: DP 4040 REFLECTGREY - Grey Reflective Paste
FEATURES	: Ready to use grey paste for obtaining reflective effect, High reflective effect at the dark, Bright and high covering feature, High washing fastness, Complies with ecologic standards.
APPLICATION	: Ready to use paste. Not suitable for coloring process. To obtain reflective design, DP 4040 REFLECTGREY should be printed on the fabric. For getting high coverage and reflective effect, product should be printed twice time or more with flash cure between each layer. % 0,5-1 of RB 2601 SUPERFIX catalyst may be added in the DP 4040 REFLECTGREY to increase and strengthen rubbing and washing fastnesses.
COLOUR	: Grey paste
РН	:7,5±0,5
VISCOSITY	: Sp:6 rpm:10 10.000-80.000 mPas (Brookfield DV II +)
SCREEN	: 34/T-43/T Threads/cm is recommended.
FIXING	: Fixing temperature and time;160°C-170°C,2–3 minutes.
CLEANING	: Screens and other equipments may be cleaned easily by pressure water.
WASHING	: It is recommended to wash reverse with sensitive programs 40°C or below.
PACKING	: Plastic Packing of 5 kg.

Note : Above mentioned qualified data is obtained from our R&D tests done in our own R&D labs. Supplied as General Knowledge and Information only and should not be considered as a Warranty Information.Printing Quality may change for different company conditions. Please start your production process after completing your own trial tests. Please stir before using the product and keep the product in room temperature.