

## **PA 1445 BONDOFLOCK PLASTISOL FLOCK ADHESIVE**

- PRODUCTS** : **PA 1445 BONDOFLOCK**–Classic Plastisol Flock Adhesive
- FEATURES** : Multi functional adhesive.  
Appropriate for %100Cotton,Cotton/Polyester Fabrics.
- APPLICATION** : Ready to use product for binding all colours of flock over fabrics. Used by mixing %4-6 PA1465 Catalyst inside the PA1445 Classic Flock adhesive. Should be printed in plenty of amounts over the fabric. When printed in plenty of amounts, flocking adhesive is well binding the flock. It is essential to start flocking without any delay after the flocking binder is printed. Fabric that flocking adhesive is applied should be placed over a metal plate, and the flocking operation should be done by well ground system flocking machine. Fixing must be immediately after that operation. Needs very well fixing.
- COLOUR** : Clear
- VISCOSITY** : (Brookfield 25°C Sp:7,Rpm:1)>1.000.000Cp(over 1.000.000cp)
- SCREEN** : 27/T Threads/cm is recommended.
- FIXING** : Fixing temperature and time;160°C-170°C,3minutes.
- CLEANING** : Screens and other equipments may be easily washed with synthetic thinner.
- WASHING** : At the 40°C, sensitive program should be applied.
- PACKING** : Plastic Packing of 6 and30kg.

Note : Above mentioned qualified data is obtained from our R&D tests done in our own R&D labs. Supplied as General Knowledge and Information only and should not be considered as a Warranty Information. Printing Quality may change for different company conditions. Please start your production process after completing your own trial tests. Please stir before using the product and keep the product in room temperature.