

TDS TECHNICAL DATA SHEETS RUBBER PRINTPASTES

RB 2535PRINTPASTE S SPECIAL WATER PASTE

PRODUCTS : **RB2535PRINTPASTES-**Special water paste, deep colours, high fastness

FEATURES: Water based pigment print paste

APPLICATION : Applied over light colured grounds, coloured by PG Group Pigmens maximum

%3. To increase and strengthen washing fastness %1-3 percentages RB 2600

OXAL or %0,5-1 percentage RB 2601 SUPERFIX Catalyst may be added.

COLOUR : Cream

PH : 9± 0,5

VISCOSITY : (Brookfield25°CSp:6,Rpm:10)20.000–50.000Cp

DENSITY : 1,04gr/ml

SCREEN : Bigger than 43/T-55/TThreads/cm is recommended.

FIXING : Fixing temperature and time;160°C-170°C,2minutes.

CLEANING: Screens and other equipments may be easily washed by pressure water.

WASHING : Reverse washing in 40C or below, Sensitive Programs.

PACKING : Plastic Packing of 60kg

Note: Above mentioned qualified data is obtained from our R&D tests done in our own R&D labs. Supplied as General Knowledge and Information only and should not be considered as a Warranty Information. Printing Quality may change for different company conditions. Please start your production process after completing your own trial tests. Please stir before using the product and keep the product in room temperature.