

TDS
TECHNICAL DATA SHEETS
RUBBER ACYLICS
WATER BASED

RB 2540 POLYPASTE

FEATURES: Pigment print paste modified by added binder and fixator. Good for

fabrics in which polyester is in bigger percentages.

APPLICATION: Applied over light coloured fabrics, coloured by PG Group pigments

maximum%3. For a much more better washing fastness % 1-3 RB 2600 or %

0,5-1 RB 2601 Catalyst should be added.

COLOUR : Cream

PH 8,5±0,5

VISCOSITY : (Brookfield25°CSp:6,Rpm:10)25.000 –90.000Cp

YOĞUNLUK : 0,98-1,1gr/ml

SCREEN : 43-T Threads/cm and bigger numbers are recomemded.

FIXING : Fixing temperature and time;160°C-170°C,2minutes.

CLEANING : Screens and other equipments may be easily washed by pressure water.

WASHING : Reverse washing in 40C or below, Sensitive Programs.

PACKING : Plastic Packing of 60 kg.

Note: Above mentioned qualified data is obtained from our R&D tests done in our own R&D labs. Supplied as General Knowledge and Information only and should not be considered as a Warranty Information. Printing Quality may change for different company conditions. Please start your production process after completing your own trial tests. Please stir before using the product and keep the product in room temperature.