



TECHNICAL DATA SHEETS RUBBER GLASS BEADS CATALYST

RB 2610 CATABEADS GLASS BEADS CATALYST

PRODUCTS: RB 2610 CATABEADS - Glass Beads Catalyst

FEATURES: A catalyst that is added to Glass Beads Adhesive, strengthens the

binding feature of glass beads. Printed fabric is durable to water

after fixing.

APPLICATION: %10 percentage RB 2610 catalyst is added to ready to use DP2735 glass beads

adhesive. Should be stirred very well before using. Mixture should be printed within one hour. Glass beads are spread after the catalyst added adhesive is printed. Before fixing, press is applied by the help of a plain material for a good binding. For to increase the efficiency of the catalyst washing should be done the

day after.

DENSITY : 1.08-1.3gr/ml

SCREEN : 27/T-43/T Treads/cm is recommended.

FIXING : Fixing temperature and time170-180°C'in 2,5-3minutes.

PACKING : Plastic Packing of 20kg

Note: Above mentioned qualified data is obtained from our R&D tests done in our own R&D labs. Supplied as General Knowledge and Information only and should not be considered as a Warranty Information. Printing Quality may change for different company conditions. Please start your production process after completing your own trial tests. Please stir before using the product and keep the product in room temperature.